

# TECHNICAL DATA SHEET



Product code: 5593

Sector: Industrial

Issue No: 2

Issue Date: 16/05/22

## OPEN GEAR COMPOUND

A straight mineral residual ideal for exposed slow moving gears.

### Application

A straight mineral residual lubricant, which is jet black in appearance. It forms a tough film on exposed surfaces, is resistant to fling, can withstand high loads, water washing and remains tacky under working conditions.

It is recommended for large exposed slow moving gears.

### Features & Benefits

- Resistant to fling
- Can withstand high loading
- Resists water washing
- Remains tacky when worked
- Heating will ease application

### Typical Characteristics

	Units	Open Gear Compound
Specific Gravity @ 15°C	Kg/l	0.99
Kinematic Viscosity @ 100°C	cSt	1050
Pour Point °C	oC max	25
Flashpoint °C	oC min	255
Fire Point °C	oC	300

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



MADE IN BRITAIN

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)