

TECHNICAL DATA SHEET



Product code: 6133

Sector: Industrial

Issue No: 3

Issue Date: 11/04/22

RUST PREVENTIVE 2670

A barium-free oil based product formulated from fully solvent refined mineral oil and selected high performance anti-corrosion additives.

Application

To be used as received and apply by brushing, dipping, swabbing or roller.

Features & Benefits

- Free of volatile organic compounds (VOC)
- Barium free
- Easy to apply
- Light viscosity promotes good coverage and excellent draining properties
- Easy removal with everyday solvents such as white spirit

Typical Characteristics

Specific Gravity @ 15°C, g/ml	0.854
Kinematic Viscosity @ 40°C, cSt	15
Flashpoint, °C	165
Film Thickness, µm	2.3
Coverage, m ² /litre	328
Humidity cabinet ASTM-D1748, days	>30
Salt spray cabinet DIN 50021, hours	16
Indoor Protection	up to 12 months
Outdoor Protection	up to 6 months

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk