

TECHNICAL DATA SHEET



Product code: 5619 **Sector:** Automotive (Passenger car & LCV) **Issue No:** 5 **Issue Date:** 01/02/24

Stop Leak 250ml

A treatment to be added to the oil in an oil system such as engine or gearbox to help minimise leaks.

Description

An oil based treatment that helps to minimise oil leaks found in systems such as the engine, gearbox or differential. Stop Leak should be used for vehicles that have obvious signs of an oil leak, or require regular top-ups. Recommended for vehicles that are losing oil on a regular basis that require topping up more often between service intervals. The treatment is compatible with fully synthetic, synthetic and mineral engine oils.

Application

Suitable for use in all petrol and diesel passenger cars and light commercial vehicles (LCV). To be used in engines, gearboxes (manual & automatic transmissions) and differentials.

Dosage Rate

1 x 250ml bottle treats:
Up to 5 litres of engine, gearbox or differential oil

Directions for use

Add contents of bottle to oil in the engine, gearbox or differential.

Typical Characteristics

Density @ 15°C, g/ml	0.870
Kinematic Viscosity @ 40°C, cSt	30.5
Flashpoint, °C	>200

Features & Benefits

- Helps minimise oil leaks in engines, gearboxes and differentials.
- Restores the performance of undamaged elastomer based seals.
- Helps maintain oil tightness of old or leaky seals.
- Rejuvenates and conditions engine seals.

Storage Instructions

Store at ambient temperature.
Avoid direct sunlight.
Product efficacy within 24 months of date on bottle if stored according to the manufacturer's instructions.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk