

**Product Code:** 5995 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 3 **Issue Date:** 01/02/24

## TRIDENT PROFESSIONAL ENGINE OIL 5w30

Semi synthetic, full SAPS, for use in petrol and diesel engines.

### Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a 5w30 viscosity meeting the below manufacturer specifications.

### Performance Profile

ACEA A3/B4, ACEA A3/B3  
API SL, CF

### Suitable for

BMW Longlife-01, BMW Longlife-98  
Fiat 9.55535-G1  
Ford WSS-M2C913-B, Ford WSS-M2C913-A  
ILSAC GF-2  
MB 229.5, MB 229.3, MB 229.1  
PSA B71-2296 <2014, PSA B71-2295  
PSA B71-2294  
Renault RN0700 / RN0710  
VW 502 00 / 505 00, VW 500 00 / 501 01  
Asian manufacturers

### Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which improves fuel economy, reduces emissions and provides extended drain capability.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

### Typical Characteristics

Density @ 15°C, g/ml	0.847
Kinematic Viscosity @ 100°C, cSt.	11.8
Flashpoint, °C	>200

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website  
[www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer