



SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 1

Compilation date: 21/04/2011

Revision date: 19/06/2017

Revision No: 1b

Section 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Product name: DIESEL POWER ECOMAX - ONE SHOT

Product code: 6206

1.2. Relevant identified uses of the substance or mixture and uses advised against

Use of substance / mixture: Diesel fuel treatment

1.3. Details of the supplier of the safety data sheet

Company name: Millers Oils Ltd
Hillside Oilworks
Rastrick Common
Brighouse
West Yorkshire
HD6 3DP
United Kingdom

Tel: +44 (0)1484 713201

Fax: +44 (0)1484 721263

Email: h.s@millersoils.co.uk

1.4. Emergency telephone number

Emergency tel: +44 (0)1484 713201

Section 2: Hazards identification

2.1. Classification of the substance or mixture

Classification under CLP: Aquatic Chronic 2: H411; Asp. Tox. 1: H304

Most important adverse effects: May be fatal if swallowed and enters airways. Toxic to aquatic life with long lasting effects.

2.2. Label elements

Label elements:

Hazard statements: H304: May be fatal if swallowed and enters airways.

H411: Toxic to aquatic life with long lasting effects.

Signal words: Danger

Hazard pictograms: GHS08: Health hazard

GHS09: Environmental

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 2



Precautionary statements: P273: Avoid release to the environment.
P301+310: IF SWALLOWED: Immediately call a POISON CENTER/doctor/.
P331: Do NOT induce vomiting.
P501: Dispose of contents/container to hazardous or special waste collection point.

2.3. Other hazards

PBT: This product is not identified as a PBT/vPvB substance.

Section 3: Composition/information on ingredients

3.2. Mixtures

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS - REACH registered number(s): 01-2119456620-43-XXXX

EINECS	CAS	PBT / WEL	CLP Classification	Percent
926-141-6	64742-47-8	-	Asp. Tox. 1: H304	70-90%

2-ETHYLHEXYL NITRATE - REACH registered number(s): 01-2119539586-27-XXXX

248-363-6	27247-96-7	-	Acute Tox. 4: H312; Aquatic Chronic 2: H411; Acute Tox. 4: H332; Acute Tox. 4: H302	10-30%
-----------	------------	---	---	--------

NAPHTHA (PETROLEUM), HEAVY AROMATIC - REACH registered number(s): 01-2119463588-24-XXXX

265-198-5	-	-	Aquatic Chronic 2: H411; Asp. Tox. 1: H304	1-10%
-----------	---	---	--	-------

NAPHTHALENE

202-049-5	91-20-3	-	Carc. 2: H351; Acute Tox. 4: H302; Aquatic Chronic 1: H410; Aquatic Acute 1: H400	<1%
-----------	---------	---	---	-----

Section 4: First aid measures

4.1. Description of first aid measures

Skin contact: Remove all contaminated clothes and footwear immediately unless stuck to skin.

Drench the affected skin with running water for 10 minutes or longer if substance is still on skin.

Eye contact: Bathe the eye with running water for 15 minutes.

Ingestion: Wash out mouth with water. Do not induce vomiting. If conscious, give half a litre of water to drink immediately. Consult a doctor.

Inhalation: Remove casualty from exposure ensuring one's own safety whilst doing so.

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 3

4.2. Most important symptoms and effects, both acute and delayed

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting.

Inhalation: No data available.

4.3. Indication of any immediate medical attention and special treatment needed

Section 5: Fire-fighting measures

5.1. Extinguishing media

Extinguishing media: Suitable extinguishing media for the surrounding fire should be used. Use water spray to cool containers.

5.2. Special hazards arising from the substance or mixture

Exposure hazards: In combustion emits toxic fumes.

5.3. Advice for fire-fighters

Advice for fire-fighters: Wear self-contained breathing apparatus. Wear protective clothing to prevent contact with skin and eyes.

Section 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

Personal precautions: Refer to section 8 of SDS for personal protection details. Turn leaking containers leak-side up to prevent the escape of liquid. Mark out the contaminated area with signs and prevent access to unauthorised personnel.

6.2. Environmental precautions

Environmental precautions: Do not discharge into drains or rivers. Contain the spillage using bunding.

6.3. Methods and material for containment and cleaning up

Clean-up procedures: Absorb into dry earth or sand. Transfer to a closable, labelled salvage container for disposal by an appropriate method.

6.4. Reference to other sections

Reference to other sections: Refer to section 8 of SDS.

Section 7: Handling and storage

7.1. Precautions for safe handling

Handling requirements: Avoid direct contact with the substance. Ensure there is sufficient ventilation of the area. Do not handle in a confined space. Avoid the formation or spread of mists in the air.

7.2. Conditions for safe storage, including any incompatibilities

Storage conditions: Store in a cool, well ventilated area. Keep container tightly closed.

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

7.3. Specific end use(s)

Section 8: Exposure controls/personal protection

8.1. Control parameters

Hazardous ingredients:

2-ETHYLHEXYL NITRATE

Workplace exposure limits:

Respirable dust

State	8 hour TWA	15 min. STEL	8 hour TWA	15 min. STEL
EU	1 ppm	1 ppm	-	-

DNEL/PNEC Values

Hazardous ingredients:

2-ETHYLHEXYL NITRATE

Type	Exposure	Value	Population	Effect
DNEL	Dermal	1 mg/kg bw/day	Workers	Systemic
DNEL	Inhalation	0.35 mg/m ³	Workers	Systemic
DNEL	Dermal	0.044 mg/cm ²	Workers	Local
DNEL	Dermal	0.52 mg/kg bw/day	Consumers	Systemic
DNEL	Inhalation	0.087 mg/m ³	Consumers	Systemic
DNEL	Oral	0.025 mg/kg bw/day	Consumers	Systemic
DNEL	Dermal	0.022 mg/cm ²	Consumers	Local
PNEC	Fresh water	0.8 ug/l	-	-
PNEC	Marine water	0.08 ug/l	-	-
PNEC	Marine sediments	0.00074 mg/kg dwt	-	-
PNEC	Soil (agricultural)	0.000191 mg/kg dwt	-	-

8.2. Exposure controls

Engineering measures: Ensure there is sufficient ventilation of the area.

Respiratory protection: Respiratory protection not required.

Hand protection: Impermeable gloves.

Eye protection: Safety glasses. Ensure eye bath is to hand.

Skin protection: Protective clothing.

Section 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

State: Liquid

Colour: Pale brown

Odour: Characteristic odour

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 5

Evaporation rate: Slow

Oxidising: Non-oxidising (by EC criteria)

Solubility in water: Insoluble

Also soluble in: Most organic solvents.

Viscosity: Non-viscous

Kinematic viscosity: 2.5 cSt

Boiling point/range°C: No data available.

Melting point/range°C: No data available.

Flammability limits %: lower: No data available.

upper: No data available.

Flash point°C: 75

Part.coeff. n-octanol/water: No data available.

Autoflammability°C: No data available.

Vapour pressure: No data available.

Relative density: 0.84

pH: No data available.

VOC g/l: No data available.

9.2. Other information

Other information: No data available.

Section 10: Stability and reactivity

10.1. Reactivity

Reactivity: Stable under recommended transport or storage conditions.

10.2. Chemical stability

Chemical stability: Stable under normal conditions.

10.3. Possibility of hazardous reactions

Hazardous reactions: Hazardous reactions will not occur under normal transport or storage conditions.

10.4. Conditions to avoid

Conditions to avoid: Heat. Flames. Sources of ignition.

10.5. Incompatible materials

Materials to avoid: Strong oxidising agents.

10.6. Hazardous decomposition products

Haz. decomp. products: In combustion emits toxic fumes.

Section 11: Toxicological information

11.1. Information on toxicological effects

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

ORL	RAT	LD50	>5000	mg/kg
-----	-----	------	-------	-------

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 6

SKN	RBT	LD50	>2000	mg/kg
-----	-----	------	-------	-------

2-ETHYLHEXYL NITRATE

ORAL	RAT	LD50	>9.6	g/kg
------	-----	------	------	------

NAPHTHALENE

ORL	MUS	LD50	316	mg/kg
ORL	RAT	LD50	490	mg/kg
SKN	RAT	LD50	>2500	mg/kg

Relevant hazards for substance:

Hazard	Route	Basis
Aspiration hazard	-	Hazardous: calculated

Symptoms / routes of exposure

Skin contact: There may be mild irritation at the site of contact.

Eye contact: There may be irritation and redness.

Ingestion: There may be soreness and redness of the mouth and throat. There may be vomiting.

Inhalation: No data available.

Section 12: Ecological information

12.1. Toxicity

Hazardous ingredients:

HYDROCARBONS, C11-14, N-ALKANES, ISOALKANES, CYCLIC, <2% AROMATICS

-	72H IC50	1-3	mg/l
-	48H EC50	1.4	mg/l
-	96H LC50	2-5	mg/l

12.2. Persistence and degradability

Persistence and degradability: Biodegradable.

12.3. Bioaccumulative potential

Bioaccumulative potential: No data available.

12.4. Mobility in soil

Mobility: Readily absorbed into soil.

12.5. Results of PBT and vPvB assessment

PBT identification: This product is not identified as a PBT/vPvB substance.

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 7

12.6. Other adverse effects

Section 13: Disposal considerations

13.1. Waste treatment methods

Disposal operations: Transfer to a suitable container and arrange for collection by specialised disposal company.

Disposal of packaging: Arrange for collection by specialised disposal company.

NB: The user's attention is drawn to the possible existence of regional or national regulations regarding disposal.

Section 14: Transport information

14.1. UN number

UN number: UN3082

14.2. UN proper shipping name

Shipping name: ENVIRONMENTALLY HAZARDOUS SUBSTANCE, LIQUID, N.O.S.
(Contains: 2-Ethylhexyl Nitrate.)

14.3. Transport hazard class(es)

Transport class: 9

14.4. Packing group

Packing group: III

14.5. Environmental hazards

Environmentally hazardous: Yes

Marine pollutant: Yes

14.6. Special precautions for user

Special precautions: No special precautions.

Section 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

15.2. Chemical Safety Assessment

Section 16: Other information

Other information

Other information: This safety data sheet is prepared in accordance with Commission Regulation (EU) No 453/2010.

This safety data sheet is prepared in accordance with Commission Regulation (EC) No 1272/2008.

Phrases used in s.2 and s.3: H302: Harmful if swallowed.

H304: May be fatal if swallowed and enters airways.

[cont...]

SAFETY DATA SHEET
DIESEL POWER ECOMAX - ONE SHOT

Page: 8

H312: Harmful in contact with skin.

H332: Harmful if inhaled.

H351: Suspected of causing cancer <state route of exposure if it is conclusively proven that no other routes of exposure cause the hazard>.

H410: Very toxic to aquatic life with long lasting effects.

H411: Toxic to aquatic life with long lasting effects.

Legal disclaimer: The above information is believed to be correct but does not purport to be all inclusive and shall be used only as a guide. This company shall not be held liable for any damage resulting from handling or from contact with the above product.