

Product Code: 7625 **Sector:** Automotive (Passenger Car & LCV) **Issue No:** 4 **Issue Date:** 17/12/25

TRIDENT PROFESSIONAL ENGINE OIL 5w40

Fully synthetic, full SAPS, for use in petrol and diesel engines.

Application

A professional engine oil suitable for the latest engine technology. Designed to meet OEM specifications. Recommended for engines requiring a 5w40 viscosity meeting the below manufacturer specifications.

Performance Profile

ACEA A3/B4
API SN PLUS, SN

Suitable for

ACEA A3/B3
API SM, SL, CF
BMW/MINI Longlife-01 (LL-01)
BMW/MINI Longlife-98 (LL-98)
Fiat 9.55535-N2
Fiat 9.55535-M2
Mercedes-Benz MB 229.5
Mercedes-Benz MB 229.3
Mercedes-Benz MB 229.1
Mercedes-Benz MB 226.5
Porsche A40
PSA B71-2296
PSA B71-2295
PSA B71-2294
Renault RN0700
Renault RN0710
VW 502 00 / 505 00
VW 500 00 / 501 01
Asian manufacturers

Features & Benefits

- Excellent low temperature flow when cold starting, helping to instantly protect vital components.
- Viscosity stability at high temperatures, delivering reduced wear and tear on the engine and its components.
- Formulated with technology to provide engine cleanliness and durability which reduces emissions and provides extended drain capability.
- Millers Oils stop start technology delivers instant protection under hot or cold conditions.

Typical Characteristics

Density @ 15°C, g/ml	0.853
Kinematic Viscosity @ 100°C, cSt.	13.6
Flashpoint, °C	>210

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer