




PRODUCT DATA SHEET



www.millersoils.co.uk

DATA SHEET NO: 7984

PRODUCT NAME/VISCOSITIES: **ZSS 2T**

DESCRIPTION:

ZSS 2T is a high performance semi-synthetic 2-stroke engine oil. It is formulated with a blend of mineral and synthetic base oils combined with ultra modern low ash additives. These are designed to give an excellent low smoke performance.

APPLICATION:

Mix with petrol as recommended by the manufacturer for petrol/oil systems or in lube injection systems. Suitable for use in all 2 stroke motorcycles, kart and scooter engines.

USER BENEFITS:

- Modern low ash / low smoke technology makes it ideal for stop / start city use
- High performance semi synthetic formulation offers maximum protection and reliability even over higher mileages
- Lubricates and helps seal piston/ring/bore to prevent power loss
- Prevents corrosion
- Suitable for road and track day use
- Meets the latest international performance specifications for two stroke engines

PERFORMANCE PROFILE:

- API TC, JASO FD, ISO-L-EGD, TISI Low Smoke

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	20
Specific Gravity @ 15°C	0.867
Kinematic Viscosity @ 100°C	7.7cSt
Pour Point °C	-30
Colour	Blue

HEALTH AND SAFETY:

Health and Safety Data Sheet 7984 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk

