



PRODUCT DATA SHEET



PRODUCT NAME/VISCOSITIES:

DATA SHEET NO: 5314

LIMITED SLIP 90

DESCRIPTION:

Solvent refined mineral base stocks treated with E.P. additive and friction modifier.

APPLICATION:

Use as received in rear axles which incorporate limited slip and require special oils.

USER BENEFITS:

- Axles which incorporate friction plates to limit the amount of 'slip' between the two driven wheels often exhibit "stick-slip" resulting in unacceptable axle noise.
- The incorporation of special friction modifying additives ensures smooth power transmission and noise reduction.
- Limited Slip Oil 90 may also be used in normal axles.

PERFORMANCE PROFILE:

- API GL5

TYPICAL CHARACTERISTICS:

SAE Viscosity Grade	SAE 90
Specific Gravity @ 15°C	0.904

HEALTH AND SAFETY:

Health and Safety Data Sheet 5314 applies to this product. When used for the purpose recommended and with due regard to the appropriate Health and Safety Data, the product should cause no concern. If in doubt, consult with Millers Oils Technical Department.

For Technical assistance call +44 (0) 1484 475060 or email technical@millersoils.co.uk



Millers Oils Ltd
Brighouse, West Yorkshire
HD6 3DP, UK
Tel: +44(0)1484 713201
www.millersoils.co.uk