Part code: 5740 **Sector:** Commercial **Issue No:** 1 **Issue Date:** 29/10/20

MAXIFLEET ENGINE OIL 15w40 PLUS

Mineral heavy duty engine oil.

Application

A cost-effective heavy duty engine oil suitable for older generation vehicles, up to and including some EURO 5 applications. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Using modern day technology for added protection in older applications
- Suitable for some automotive applications ideal for use in mixed fleets
- A multiple application product suitable for use in both on and off road applications

Typical Characteristics

Density @ 15°C, g/ml	0.879
Kinematic Viscosity @ 100°C, cSt	14
Flashpoint, °C	>200
TBN, mgKOH/g	9

Technical & Health and Safety

T: 01484 475060
E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Performance Profile

ACEA E7
API CI-4, CH, CF, SJ
Allison C4
CAT TO-2, CAT ECF-1a
Deutz DQC I
MACK EOL+
MAN 271
Mercedes Benz MB 228.3
MTU Type 2
Renault RD
Volvo VDS
ZF TE-ML-06F, ZF-TE-ML-07B

Suitable for

ACEA E3, E2
API CG-4, CF-4, CD, SG, SF
MACK EOK/2
Mercedes Benz MB 228.1
MTU Type 1

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer