

Part code: 7745

Sector: Commercial Vehicle

Issue No: 5

Issue Date: 17/10/24

## TRUCKMASTER ENGINE OIL 5w30

Fully synthetic, low SAPS

### Application

A premium heavy duty engine oil suitable for the latest engine and exhaust after treatment technology. Designed to meet the stated manufacturer specifications.

### Features & Benefits

- Lower viscosity grade improves fuel economy vs. higher viscosity oils.
- Excellent cold flow properties on startup protecting vital components.
- Dynamic Fluid Technology enhances viscosity stability at high temperatures maximizing oil film protection under all conditions.
- Low SAPS technology delivering protection of catalysts, DPF's and EGR's to aid in reducing emissions.
- Extended drain capabilities where applicable, increasing interval periods.
- Bio fuel and gas compatible offering product rationalisation and reducing misapplication.

### Typical Characteristics

Density @ 15°C, g/ml	0.856
Kinematic Viscosity @ 100°C, cSt	12
Flashpoint, °C	>200
TBN, mgKOH/g	10

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website

[www.millersoils.co.uk](http://www.millersoils.co.uk)

### Performance Profile

ACEA E6, E7, E8, E9, E11  
API CK-4  
CAT ECF-3  
Cummins CES 20086  
Detroit Diesel DDC 93K222  
Deutz DQC IV-18 LA, DQC III-18 LA  
MACK EOS-4.5  
MAN M 3677, M 3775, M 3477, M 3271-1  
Mercedes Benz MB 228.52, MB 228.51  
MTU Type 3.1  
Renault RLD-3, RLD-4  
Scania LDF-4  
Volvo VDS-4.5

### Suitable for

API CJ-4, CI-4 Plus, CI-4, SN Plus  
CAT ECF-2, ECF-1a  
Cummins CES 20081  
DAF E6, E9  
Detroit Diesel DDC 93K218  
Deutz DQC IV-10 LA, DQC III-10 LA, DQC II-10 LA  
FORD WSS M2C213-A1  
IVECO 18-1804 TLS E6  
JASO DH-2  
MACK EO-OP+, EO-N, EO-M+  
MAN M 3575  
Mercedes Benz MB 228.31, MB 226.9, MB 235.28  
MTU Type 2.1  
Renault RLD-2, RLD, RGD, RXD  
Scania LA  
Voith Retarder Class B  
Volvo VDS-5\*, VDS-4, VDS-3, VDS-2, VDS, CNG

\*This product can be used where Volvo VDS-5 specification is required with the exception of potential fuel economy benefits. Always consult vehicle handbook for oil change intervals.

**Footnotes:** SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer