

TECHNICAL DATA SHEET



Product code: 7997 Sector: Automotive

Issue No: 1

Issue Date: 11/08/20

XF PREMIUM ENGINE OIL C2 0w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A premium engine oil formulated using the latest technology for OEM applications requiring a C2 0w30 viscosity, predominantly for PSA group applications including Peugeot, Citroen and DS.

Performance Profile

ACEA C2
PSA B71-2312

Suitable for

API SN
Chrysler MS-90047, Chrysler MS-13340
Fiat 9.55535-GS1, Fiat 9.55535-DS1
Peugeot, Citroen, DS
Asian manufacturers
Millers Oils underwrites this product for
BMW Longlife-12 FE applications

Typical Characteristics

Density @ 15°C, g/ml	0.846
Kinematic Viscosity @ 100°C, cSt.	9.9
Flashpoint, °C	>200

Features & Benefits

- XF Premium engine oil with Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT delivers outstanding LSPI (Low Speed Pre-Ignition) protection and our ultimate in turbo charger care, even under the most extreme operating conditions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM - Original Equipment Manufacturer



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk