

TECHNICAL DATA SHEET



Part code: 8193

Sector: Commercial

Issue No: 1

Issue Date: 29/10/20

MAXIFLEET ENGINE OIL 15w40

Mineral heavy duty engine oil.

Application

A cost-effective heavy duty engine oil suitable for older generation vehicles. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Using modern day technology for added protection in older applications
- Suitable for some automotive applications ideal for use in mixed fleets
- A multiple application product suitable for use in both on and off road applications

Typical Characteristics

Density @ 15°C, g/ml	0.876
Kinematic Viscosity @ 100°C, cSt	14
Flashpoint, °C	>200
TBN, mgKOH/g	7

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Performance Profile

ACEA E2
API CF-4, CF, SJ
Allison C4
CAT TO-2
Deutz DQC I
MACK EOK/2
MAN 271
Mercedes Benz MB 228.1
MIL-L-2104E, MIL-L-2104D, MIL-L-2104C, MIL-L-46152D
MTU Type 1
Volvo VDS
ZF TE-ML-06F, ZF-TE-ML-07B

Suitable for

API CD, SG, SF

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer



MADE IN BRITAIN

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk