

Part code: 5733 Sector: Commercial

Issue No: 1 Issue Date: 29/10/20

MAXIFLEET ENGINE OIL 10w30

Mineral heavy duty engine oil.

Application

A cost-effective heavy duty engine oil suitable for older generation vehicles, up to and including EURO 3. Designed to meet the stated manufacturer specifications.

Features & Benefits

- Using modern day technology for added protection in older applications
- Suitable for some automotive applications ideal for use in mixed fleets
- A multiple application product suitable for use in both on and off road applications

Typical Characteristics

Density @ 15°C, g/ml	0.865
Kinematic Viscosity @ 100°C, cSt	11.5
Flashpoint, °C	>200
TBN, mgKOH/g	8

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Performance Profile

ACEA E2
API CG-4, CF, SJ
Allison C4
CAT TO-2
Deutz DQC I
MACK EOL+
MAN 271
Mercedes Benz MB 228.1
MIL-L-46152E
MTU Type 1
Volvo VDS
ZF TE-ML-06F, ZF TE-ML-07B

Suitable for

API CF-4, CD, SG, SF
MACK EOK/2

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer



MADE IN BRITAIN 

Millers Oils Ltd
Brighouse West Yorkshire HD6 3DP UK
Tel: +44(0) 1484 713201
www.millersoils.co.uk