

# TECHNICAL DATA SHEET



Part code: 5728

Sector: Commercial

Issue No: 1

Issue Date: 29/10/20

## MAXIFLEET ENGINE OIL 30

Monograde heavy duty engine oil.

### Application

A heavy duty engine oil suitable for older generation vehicles and classic equipment. Designed to meet the stated manufacturer specifications.

### Features & Benefits

- Using modern day technology for added protection in older applications
- A multiple application product suitable for use in both on and off road including hydraulic and transmission applications

### Performance Profile

API CF-2, CF, SG  
Allison C3  
CAT TO-2  
MAN 270  
Mercedes Benz MB 228.0  
MIL-L-2104C, MIL-L-2104B, MIL-L-46152B  
ZF TE-ML-02H

### Suitable for

API CD, CC, SF, SE

### Typical Characteristics

Density @ 15°C, g/ml	0.885
Kinematic Viscosity @ 100°C, cSt	11
Flashpoint, °C	>200
TBN, mgKOH/g	7

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer



**MADE IN BRITAIN**

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)