

# TECHNICAL DATA SHEET



Product code: 5862 Sector: Automotive

Issue No: 1

Issue Date: 11/08/20

## XF PREMIUM ENGINE OIL C3 VW 5w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

### Application

A premium OEM approved engine oil formulated using Millers Oils Dynamic Fluid Technology (DFT) for applications requiring a C3 5w30 viscosity. Designed for Volkswagen Audi Group (VAG) including Bentley, Lamborghini, Seat, Skoda and Porsche. Other coverage includes BMW and Mercedes Benz.

### Performance Profile

ACEA C3  
API SN  
BMW Longlife-04  
MB 229.51  
Porsche C30  
**VW 504 00 / 507 00 (Approved)**

### Suitable for

Chrysler MS-11106  
Fiat 9.55535-S3  
MB 229.31  
VW 506 00 / 506 01, VW 503 00 / 503 01  
VW 502 00 / 505 01, VW 502 00 / 505 00  
VW 500 00 / 501 01  
Audi, Bentley, Lamborghini, Seat, Skoda  
Asian manufacturers

### Typical Characteristics

Density @ 15°C, g/ml	0.850
Kinematic Viscosity @ 100°C, cSt.	11.7
Flashpoint, °C	>200

### Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).
- Compatible for use with bio fuels, DFT provides exceptional performance and protection against deposits, sludge and engine wear.

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website

[www.millersoils.co.uk](http://www.millersoils.co.uk)

**Footnotes:** SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology. OEM - Original Equipment Manufacturer.  
Asian manufacturers – Including but not limited to Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki and Toyota.



**MADE IN BRITAIN**

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)