TECHNICAL DATA SHEET



Product code: 6230 Sector: Automotive Issue Date: 11/08/20 Issue No: 1

XF PREMIUM ENGINE OIL C2/C3 5w30

Fully synthetic, mid SAPS, for use in petrol, diesel and hybrid engines.

Application

A premium OEM approved engine oil formulated using the latest technology for applications requiring C2 or C3 5w30 viscosities. Covering European manufacturers including BMW, Mercedes Benz and GM dexos 2 applications.

Performance Profile

API SN ACEA C2/C3

BMW Longlife-04 (Approved) MB 229.52 (Approved), MB 229.51 Opel/Vauxhall OV0401547 (Approved)

Renault RN0700 / RN0710

Suitable for

API CF Chrysler MS-11106 Fiat 9.55535-S3, Fiat 9.55535-S1 GM dexos 2, GM-LL-B-025, GM-LL-A-025 MB 229.31, MB 226.5 PSA B71-2290 <2014 VW 502 00 / 505 01, VW 502 00 / 505 00 VW 500 00 / 501 01 Dacia Asian manufacturers

Typical Characteristics

0.848 Density @ 15°C, g/ml Kinematic Viscosity @ 100°C, cSt. 12.0 Flashpoint, °C >200

Features & Benefits

- XF Premium engine oil with Millers Oils Dynamic Fluid Technology (DFT) provides enhanced low temperature flow when cold starting, instantly protecting the vital components of the engine from the very start of every journey.
- XF Premium engine oil with DFT maximises viscosity stability at high temperatures. This reduces engine wear giving superior protection for components including pistons, rings, timing chain, bearings and valve lifters.
- DFT specifically engineered to enhance engine cleanliness, delivering improved fuel economy, reduced emissions and extended service drain capability
- DFT complements and utilises latest mid SAPS technology protecting after treatment systems such as particulate filters, Selective Catalytic Reduction (SCR) and AdBlue delivering our ultimate soot control and environmental protection.
- DFT delivers outstanding instant protection under hot and cold temperatures, whilst simultaneously reducing fuel consumption and lowering exhaust emissions.
- XF Premium engine oil with DFT is specifically formulated for use in all hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, DFT – Dynamic Fluid Technology, OEM - Original Equipment Manufacturer. Asian manufacturers - Including but not limited to Honda, Hyundai, Infiniti, Kia, Lexus, Nissan, Suzuki and Toyota.







