TECHNICAL DATA SHEET



Product code: 8209 Sector: Automotive (Passenger Car & LCV) Issue No: 4 Issue Date: 01/02/24

EE PERFORMANCE ENGINE OIL 5w50

Fully synthetic, full SAPS, for use in petrol and diesel engines.

Application

A performance engine oil featuring NANODRIVE low friction technology for vehicles requiring an A3/B4 or A3/B3 5w50 specification.

Recommended for Mercedes Benz AMG powered vehicles, Porsches, Caterhams and Fords including the Mustang.

Recommended for

ACEA A3/B4, ACEA A3/B3 API SN, SM, SL Ford WSS-M2C931-C MB 229.3, MB 229.1 Porsche A40 Alpina, AMG, Aston Martin, Caterham, Cosworth, Ferrari, Lotus, Renault, TVR Asian manufacturers

Typical Characteristics

Density @ 15°C, g/ml 0.850 Kinematic Viscosity @ 100°C, cSt. 18.4 Flashpoint, °C >200

Features & Benefits

- Increased engine power and torque from award winning NANODRIVE low friction technology and synthetic ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- "Track day ready", high performance oil; delivers maximum engine performance whilst meeting manufacturer's specifications and recommended oil drain interval for on-road use.
- Full SAPS oil combined with NANODRIVE technology gives ultimate engine protection.
- Higher viscosity grade provides stable oil film and lubrication throughout full RPM range in arduous applications including track day use.

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website www.millersoils.co.uk

Footnotes: SAPS – Sulphated Ash, Phosphorus & Sulphur, OEM - Original Equipment Manufacturer. Asian manufacturers – Including but not limited to Daihatsu, Honda, Hyundai, Infiniti, Kia, Lexus, Mazda, Mitsubishi, Nissan, Subaru, Suzuki and Toyota.