

Product code: 8327 **Sector:** Automotive (Passenger car & LCV) **Issue No:** 1 **Issue Date:** 03/04/23

EE Performance MTF 75w

Fully synthetic gear oil with ester technology for use in gearboxes.

Application

A performance gear oil featuring NANODRIVE low friction technology to provide maximum protection and fuel economy. Predominantly for European and Asian manufacturers.

Suitable for

API GL-4

BMW Group Inc. Mini, Rolls Royce MTF LT-3,
P/N 83 22 0 397 244
Fiat Chrysler Automobiles Inc. Abarth,
Alfa Romeo, Chrysler, Dodge, Ferrari, Fiat,
Jeep, Lancia, Maserati, Ram (pre-2021)
9.55550-MZ6, 9.55550-MZ2
Ford M2C200-E1, M2C200-D3, M2C200-D2
General Motors Inc. Buick, Cadillac, Chevrolet,
GMC, Opel, Saturn, Vauxhall (pre-2017),
GM 19259104/19259105 (BOT 303),
1940004 (BOT 303)
Nissan P/N 999MP-TF0870P
PSA Inc. Peugeot, Citroen, DS,
B71 2316, P/N 9730.A8, P/N 1618078480,
VW Group Inc. Audi, Seat, Skoda, VW
TL 726 P/N G 070 726, TL 726 P/N G 060 726,
TL 726 P/N G 055 726, TL 726 P/N G 052 726,
TL 525 27 P/N G 052 527, P/N G 055 512,
TL 525 12 P/N G 052 512,
TL 521 78 P/N G 052 178,
TL 521 71 P/N G 052 171,
Porsche P/N 000.043.301.36

BOT 350 M3
BOT 303
TF 0870
Tranself NFX

Features & Benefits

- Reduced driveline losses from award winning NANODRIVE low friction technology, synthetic base oil with Ester formulation.
- Extended component life and reduced operating temperatures as a result of the instant lubrication provided by NANODRIVE low friction technology.
- "Track day ready", high performance oil; delivers maximum performance whilst meeting manufacturer's specifications and recommended oil drain interval for on-road use.
- Maximised efficiency and MPG delivered from the combined low viscosity and low friction NANODRIVE formulation.
- Synthetic base oil and Ester combined with NANODRIVE technology gives ultimate component protection.
- EE Performance gear oil is specifically formulated for use in hybrid systems including self-charging hybrid electric vehicles (HEV) and plug in hybrid electric vehicles (PHEV).
- Covers a wide range of manufacturers including the latest gearbox technology.

Typical Characteristics

Density @ 15°C, g/ml	0.851
Kinematic Viscosity @ 100°C, cSt	6.3
Flash Point, °C	>200

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk

Footnotes: P/N – OEM Part Number