



XF PREMIUM RANGE

XF premium is a range of fully synthetic engine oils featuring Dynamic Fluid Technology (DFT), and focuses on maximising fuel economy whilst minimising engine wear.

DYNAMIC FLUID TECHNOLOGY

Dynamic Fluid Technology (DFT) is the unique, superior lubrication technology developed and blended by Millers Oils.

PROTECTS ON:



START UP

STOP START





SHORT JOURNEYS

LONG JOURNEYS

DFT utilises the very latest and best additive technologies, expertly formulated by our team of chemists, to act synergistically in delivering maximised protection and enhanced performance for your engine.

DFT is particularly advantageous during the start-up phase, when engines are most susceptible to damage and wear. Modern driving conditions exacerbate this vulnerability, with Stop Start technology and short journeys resulting in reduced engine life. DFT combats these effects, exploiting the molecules' surface chemistry to form a dynamic protective film over all component surfaces, and safeguarding the engine.



0w16 Code 8174

For use in petrol and hybrid engines. A premium gasoline engine oil formulated using the latest technology for OEM applications requiring a 0w16 viscosity, which provides protection against low speed pre-ignition (LSPI) and timing chain wear. Ideally suited for Honda, Lexus, Nissan, Suzuki, Toyota and other Asian manufacturers.



C5/C6 0w20 Code 8175

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil* formulated using the latest technology for applications requiring a C5 0w20 viscosity, Designed predominantly for BMW, Ford, Jaguar Land Rover, Opel/Vauxhall, Volvo and Asian manufacturers.



C5 VW 0w20 Code 8049

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil* formulated using the latest technology for applications requiring a C5 0w20 viscosity designed for Volkswagen Audi Group (VAG) including Bentley, Seat, Skoda and Porsche.



C3 VW 0w30 Code 7998

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil* formulated using the latest technology for applications requiring a C3 0w30 viscosity, designed for Volkswagen Audi Group (VAG) including Lamborghini, Seat, Skoda and Porsche.



C1 5w30 Code 6228

Low SAPS, for use in petrol, diesel and hybrid engines.

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a C1 5w30 viscosity, predominantly for Land Rover/Range Rover vehicles fitted with Diesel Particulate Filters (DPF).



C2 5w30 Code 6229

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium engine oil formulated using the latest technology for OEM applications requiring a C2 5w30 viscosity, predominantly for PSA group applications including Peugeot, Citroen and DS.



C5 EC0 5w20 Code 7779

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a C5 5w20 viscosity, introduced for Ford Eco-Boost petrol engines and Jaguar Land Rover.



C2 0w30 Code 7997

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium engine oil formulated using the latest technology for OEM applications requiring a C2 0w30 viscosity, predominantly for PSA group applications including Peugeot, Citroen and DS.



C2 EC0 0w30

Code 8045

Mid SAPS, for use in petrol, diesel and hybrid engines

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a C2 0w30 viscosity, predominantly for Ford and Jaguar Land Rover.



C2/C3 5w30 Code 6230

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil* formulated using the latest technology for applications requiring C2 or C3 5w30 viscosities. Covering European manufacturers including BMW, Mercedes Benz and GM dexos 2 applications.



C3 VW 5w30 5862

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil* formulated using the latest technology for applications requiring a C3 5w30 viscosity. Designed for Volkswagen Audi Group (VAG) including Bentley, Lamborghini, Seat, Skoda and Porsche. Other coverage includes BMW and Mercedes Benz.



C3 RN 5w30 8343

A synthetic oil designed for most gasoline engines (except Renault Sport & Alpine) and the Euro 6 diesel engine (2018 onwards). Suitable for use in vehicles where a Renault RN 17 specification 5w30 lubricant is required. Replaces older Renault specifications RN700 and RN710 (backwards compatible). Designed for turbocharged petrol direct (TGDI) engines and includes Petrol Particulate Filter (PPF) protection and specific tests to ensure oxidation performance; piston cleanliness and sooted valvetrain wear performance.

For details of our full approvals and performance specifications please refer to page 8. OEM - Original Equipment Manufacturer.

Asian manufacturers - including but not limited to, Honda, Hyundai, Infinity, Kia, Lexus, Nissan, Suzuki and Toyota. SAPS - Sulphated, Ash, Phosphorus, Sulphur.

* Approval pending.



C4 5w30 6231

Low SAPS, for use in petrol, diesel and hybrid engines.

A premium engine oil formulated using the latest technology for OEM applications requiring a C4 5w30 viscosity, predominantly for Renault diesel powered vehicles including Mercedes Benz and Nissan.



ECO 5w30 Code 6221

Full SAPS, for use in petrol, diesel and hybrid engines.

A premium manufacturer acknowledged engine oil formulated using the latest technology for OEM applications requiring a 5w30 viscosity, predominantly for Ford, Jaguar Land Rover and Asian manufacturers.



LSPI 5w30 Code 8099

For use in petrol and hybrid engines.

A premium gasoline engine oil formulated using the latest technology for OEM applications requiring a GM dexos 1 Gen 2 in a 5w30 viscosity, which provides protection against low speed pre-ignition (LSPI) and timing chain wear. Ideally suited for Opel Vauxhall and Asian manufactures including Lexus, Nissan, Suzuki and Toyota.



0w40 Code 7725

Full SAPS, for use in petrol, diesel and hybrid engines.

A premium engine oil formulated using the latest technology for OEM applications requiring a 0w40 viscosity, predominantly for use in Mercedes Benz, Mercedes Benz AMG powered vehicles, Porsche and Renault.



C3 5w40 Code 7640

Mid SAPS, for use in petrol, diesel and hybrid engines.

A premium OEM approved engine oil formulated using the latest technology for applications requiring a C3 5w40 viscosity. Targeting 'Pumpe Düse' PD engines and other VAG engines including Volkswagen Audi Group, Lamborghini, Seat and Skoda. Other coverage includes GM and Mercedes Benz.



5w50 Code 7726

Full SAPS, for use in petrol and diesel engines.

A premium engine oil formulated using the latest technology for OEM applications requiring a 5w50 viscosity. Recommended for Mercedes Benz AMG powered vehicles, Porsche, Caterhams and Fords including the Mustang.













FOR PRODUCT SPECIFICATION INFO & TECHNICAL HELP PLEASE CALL US ON +44 (0) 1484 475060

PRODUCT CODE	PRODUCT	SAPS LEVEL		APPLICATIONS												
			API	ACEA	ILSAC	BMW	FIAT	FORD & JLR	GM	MB	OPEL / VAUXHALL	PSA‡	RENAULT	VAG* & Porsche	VOLVO	OTHER
8174	XF PREMIUM ENGINE OIL 0w16	_	SP, SP RC, SN PLUS RC, SN PLUS, SN RC, SN	_	ILSAC GF-6B											Asian manufacturers
8175	XF PREMIUM ENGINE OIL C5/C6 0w20	Mid SAPS	SP, SP RC SN PLUS RC, SN PLUS, SN, SM	C5/C6	ILSAC GF-6A ILSAC GF-5 ILSAC GF-4	BMW Longlife-17 FE+ BMW Longlife-14 FE+	Fiat 9.55535-GSX	Ford WSS-M2C947-B1 Ford WSS-M2C962-A1 Jaguar Land Rover STJLR.03.5006 Jaguar Land Rover STJLR.51.5122		MB 229.72 MB 229.71	Opel/Vauxhall OV0401547 **				Volvo VCC RBS0-2AE§	Chrysler MS-6395, Chrysler MS-12145, Asian manufacturers
8049	XF PREMIUM ENGINE OIL C5 VW 0w20	Mid SAPS	_	C5	_									Porsche C20 vw 508 00 / 509 00		
7779	XF PREMIUM ENGINE OIL C5 EC0 5w20	Mid SAPS	SN RC, SN	C5 A1/B1	ILSAC GF-4 ILSAC GF-5		Fiat 9.55535-CR1	Ford WSS-M2C945-A Ford WSS-M2C948-B Ford WSS-M2C948-A Ford WSS-M2C925-B Ford WSS-M2C925-A Jaguar Land Rover STJLR.03.5004								Chrysler MS-6395 Asian manufacturers
7997	XF PREMIUM ENGINE OIL C2 0w30	Mid SAPS	SN	C2	_	BMW Longlife-12 FE *	Fiat 9.55535-GS1 Fiat 9.55535-DS1					PSA B71-2312				Chrysler MS-90047 Chrysler MS-13340 Asian manufacturers
8045	XF PREMIUM ENGINE OIL C2 ECO 0w30	Mid SAPS	SN	C2	-			Ford WSS-M2C950-A Jaguar Land Rover STJLR.03.5007								Asian manufacturers
7998	XF PREMIUM ENGINE OIL C3 VW 0w30	Mid SAPS	SN	C3	_									Porsche C30 VW 504 00 / 507 00 VW 506 00 / 506 01 VW 503 00 / 503 01 VW 502 00 / 505 01 VW 502 00 / 505 00 VW 500 00 / 501 01		

^{*} Millers Oils underwrites this product for BMW Longlife-12 FE applications

§ Engine tests only

Red represents specifications holding a formal OEM approval/acknowledgement/approval pending

All products available in 1L, 5L, 20L, 60L, 199L, 1000L and Bulk

For more information on our full automotive product range please visit our website, or contact us directly on 01484 713201

^{** 0}V0401547 suitable for use in dexos 2 or dexos D

^{***} VCC 95200377 suitable for use where a 0w30 viscosity is recommended (except fuel economy benefit)

[†] VAG - Volkswagen Audi Group inc. Bentley, Lamborghini, Seat, Skoda and Porsche.

‡ PSA - Peugeot Société Anonyme inc. Citroën, DS and Peugeot. PSA bought Vauxhall Opel in March 2017 any vehicle manufactured after this time may have to follow PSA specification.

PRODUCT CODE	PRODUCT	SAPS LEVEL														
			API	ACEA	ILSAC	BMW	FIAT	FORD & JLR	GM	MB	OPEL/ VAUXHALL	PSA‡	RENAULT	VAG* & Porsche	VOLVO	OTHER
6228	XF PREMIUM ENGINE OIL C1 5w30	Low SAPS	_	C1	_			Ford WSS-M2C934-B Jaguar Land Rover STJLR.03.5005								JASO DL-1 Asian manufacturers
6229	XF PREMIUM ENGINE OIL C2 5w30	Mid SAPS	SN, CF	C2	-		Fiat 9.55535-S1					PSA B71-2290				Asian manufacturers
6230	XF PREMIUM ENGINE C2/C3 5w30	Mid SAPS	SN, CF	C2/C3	_	BMW Longlife-04	Fiat 9.55535-S3 Fiat 9.55535-S1		GM dexos 2 GM-LL-B-025 GM-LL-A-025	MB 229.52 MB 229.51 MB 229.31 MB 226.5	Opel/Vauxhall OV0401547	PSA B71-2290 <2014	RN0700 RN0710	VW 502 00 / 505 01 VW 502 00 / 505 00 VW 500 00 / 501 01		Chrysler MS-11106 Dacia Asian manufacturers
5862	XF PREMIUM ENGINE OIL C3 VW 5w30	Mid SAPS	SN	C3	-	BMW Longlife-04	Fiat 9.55535-S3			MB 229.51 MB 229.31				Porsche C30 VW 504 00 / 507 00 VW 506 00 / 506 01 VW 503 00 / 503 01 VW 502 00 / 505 01 VW 502 00 / 505 00 VW 500 00 / 501 01		Chrysler MS-11106 Asian manufacturers
8343	XF PREMIUM ENGINE OIL C3 RN 5w30	Mid SAPS	_	C3	_								RN17 RN0710 RN0700			Dacia Samsung
6231	XF PREMIUM ENGINE OIL C4 5w30	Low SAPS	-	C4	_		Fiat 9.55535-S4			MB 229.51 MB 229.31 MB 226.51			RN0720			Dacia Asian manufacturers
6221	XF PREMIUM ENGINE OIL ECO 5w30	Full SAPS	SL, CF	A5/B5 A1/B1	ILSAC GF-4		Fiat 9.55535-G1	Ford WSS-M2C913-D Ford WSS-M2C913-C Ford WSS-M2C913-B Ford WSS-M2C913-A Jaguar Land Rover STJLR.03.5003					RN0700		Volvo VCC 95200377 ***	Dacia Asian manufacturers
8099	XF PREMIUM ENGINE OIL LSPI 5w30	_	SP, SP RC, SN PLUS RC, SN PLUS, SN RC, SN	_	ILSAC GF-6A ILSAC GF-5 ILSAC GF-4		Fiat 9.55535-CR1	Ford WSS-M2C961-A1 Ford WSS-M2C946-B1 Ford WSS-M2C946-A Ford WSS-M2C929-A	GM dexos 1 Gen 2 GM dexos 1 Gen 1 GM 6094M GM 4718M							Chrysler MS-6395 Asian manufacturers
7725	XF PREMIUM ENGINE OIL 0w40	Full SAPS	SN, CF	A3/B4 A3/B3	_	BMW Longlife-01 BMW Longlife-98	Fiat 9.55535-Z2 Fiat 9.55535-M2	Ford WSS-M2C937-A	GM-LL-B-025 GM-LL-A-025	MB 229.5 MB 229.3 MB 229.1			RN0700 RN0710	Porsche A40 VW 502 00 / 505 00 VW 500 00 / 501 01	Volvo VCC 95200356	AMG Chrysler MS-12633 (SRT) Chrysler MS-10725 SAAB Asian manufacturers
7640	XF PREMIUM ENGINE OIL C3 5w40	Mid SAPS	SN, CF	C3	-	BMW Longlife-04	Fiat 9.55535-GH2 Fiat 9.55535-T2 Fiat 9.55535-S2	Ford WSS-M2C917-A	GM dexos 2 GM-LL-B-025 GM-LL-A-025	MB 229.52 MB 229.51 MB 229.31 MB 226.5	Opel/Vauxhall OV0401547		RN0700 RN0710	Porsche C40 Porsche A40 VW 511 00 VW 502 00 / 505 01 VW 502 00 / 505 00 VW 500 00 / 501 01		Chrysler MS-11106 Asian manufacturers
7726	XF PREMIUM ENGINE OIL 5w50	Full SAPS	SN,SM,SL	A3/B4 A3/B3	-			Ford WSS-M2C931-C		MB 229.3 MB 229.1				Porsche A40		AMG Caterham Cosworth Asian manufacturers

§ Engine tests only
Red represents specifications holding a formal OEM approval/acknowledgement/approval pending

All products available in 1L, 5L, 20L, 60L, 199L, 1000L and Bulk For more information on our full automotive product range please visit our website, or contact us directly on 01484 713201



^{*} Millers Oils underwrites this product for BMW Longlife-12 FE applications

** 0V0401547 suitable for use in dexos 2 or dexos D

*** VCC 95200377 suitable for use where a 0w30 viscosity is recommended (except fuel economy benefit)

† VAG – Volkswagen Audi Group inc. Bentley, Lamborghini, Seat, Skoda and Porsche.

‡ PSA - Peugeot Société Anonyme inc. Citroën, DS and Peugeot. PSA bought Vauxhall Opel in March 2017 any vehicle manufactured after this time may have to follow PSA specification.



WHICH OIL?

The popular Millers Oils 'Which Oil?' guide can be found on our website. We want to make sure that people know which oil to use and the oil selector makes that very easy. Users can find out which oil they need by either entering their registration plate or typing in the make and model.

To use our Which Oil? guide visit: www.millersoils.co.uk

Millers Oils Head Office

Millers Oils Ltd Brighouse, West Yorkshire, HD6 3DP, UK T:+44 (0) 1484 713201 F:+44 (0) 1484 721263 E:sales@millersoils.co.uk E:international@millersoils.co.uk

Millers Oils Scotland

T: +44 (0) 1236 280107 E: glasgow@millersoils.co.uk

Technical & Support

T: 01484 475060 E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website

www.millersoils.co.uk













MillersOilsLtd

All products and information are reflective of the latest specifications at the time of going to print. The company reserves the right to change formulations and specifications without prior notice. Product images are shown for illustration purposes only.

