

Part code: 8339

Sector: Commercial Vehicle

Issue No: 3

Issue Date: 01/06/24

MULTIFLEET ATF UNIVERSAL

Automatic transmission oil for commercial vehicles

Application

A universal lubricant for the majority of automatic transmissions.

Suitable for

Allison C4 (TES 228), Allison C3
Bosch TE-ML 09
Cat TO-2
Ford WSS M2C166H, M2C138CJ, Ford Mercon
GM Dexron IID, GM Dexron II
GM Type A Suffix A (TASA)
Hagglunds Denison HF-O Hydraulic Systems
MAN M339 Type Z1, MAN M339 Type V1, MAN
M339 Type L2, MAN M339 Type L1
MB 236.9, MB 236.7, MB 236.6, MB 236.5, MB
236.3, 236.2, 236.1
Renk-Doromat Transmission Systems
Sperry-Vickers Systems
Sundstrand Systems
Voith H55.6635.XX
ZF TE-ML 02F, 03D, 04D, 05L, 09B, 11A, 11B,
14A, 17C
Suitable for Power Steering Applications

Features & Benefits

- Provides a universal lubricant for the majority of automatic transmissions
- Good low temperature properties
- Ideal for hydraulic systems, especially those exposed to wide temperature variations

Typical Characteristics

Density @ 15°C, g/ml	0.857
Kinematic Viscosity @ 100°C, cSt	7.3
Flashpoint, °C	>200
Colour	Red

Technical & Health and Safety

T: 01484 475060

E: technical@millersoils.co.uk

For H&S info or SDS, please visit our website
www.millersoils.co.uk