

# TECHNICAL DATA SHEET



Product code: 8470

Sector: Industrial

Issue No: 1

Issue Date: 30/08/23

## MILLICUT CAS 30

A neat cutting oil blended from high quality solvent refined mineral oil and high lubricity EP extreme pressure additives.

### Application

Use as received for a range of arduous machining operations and difficult to machine metals.

### Features & Benefits

- Enhanced high levels of EP additive promotes excellent tool life.
- Suitable for arduous machining of stainless steel.
- Pale colour provides good work piece visibility.
- Good results as a metal pressing lubricant.

### Typical Characteristics

Density @ 15°C, g/ml	0.889
Kinematic Viscosity @ 40°C, cSt	30
Flashpoint, °C	>200
Copper Corrosion Test (ASTM130), rating	3b

### Technical & Health and Safety

T: 01484 475060

E: [technical@millersoils.co.uk](mailto:technical@millersoils.co.uk)

For H&S info or SDS, please visit our website [www.millersoils.co.uk](http://www.millersoils.co.uk)



MADE IN BRITAIN

Millers Oils Ltd  
Brighouse West Yorkshire HD6 3DP UK  
Tel: +44(0) 1484 713201  
[www.millersoils.co.uk](http://www.millersoils.co.uk)