

Product code: 8464

Sector: Industrial

Issue No: 1

Issue Date: 22/08/25

Millmax Longlife HV 68

Millmax Longlife HV 68 is a premium energy efficient hydraulic oil developed using the highest quality GII base oils and complementary additive technologies, creating a long-lasting, high-performance hydraulic oil. Meeting stringent OEM standards such as Bosch Rexroth RDE 90235 and Parker HF-0, Millmax Longlife HV 68 ensures hydraulic system durability and longevity.

Application

Suitable for use in a wide range of applications including industrial hydraulic systems requiring load-carrying capability.

Features & Benefits

- Potential service life in excess of 4,500 hours, reaching up to 7,000 hours with regular sampling
- High viscosity index promotes energy efficiency
- Excellent resistance to compression allows for superb power transfer
- Zinc-based anti-wear properties extend equipment lifespan by protecting components from wear
- Excellent thermal and oxidation stability helps maintain system cleanliness over extended periods
- Low-foaming formula reduces aeration and cavitation, ensuring reliable power transfer
- Demulsification prevents water contamination that could lead to rust, corrosion and reduced lubricity
- Compatible with elastomers and seals, promoting longer seal life and minimising maintenance needs

Performance Profile

- DIN 51524-3 (HVLPI)
- ISO 11158 (HV)
- ASTM D6158
- SAE MS 1004
- GB 11118.1-2011
- GM LS-2
- AIST 126, 127
- SEB 181222
- Bosch Rexroth RDE 90235
- Parker HF-0, HF-1, HF-2
- Eaton E-FDGN-TB002-E
- Fives Cincinnati P69

Typical Characteristics

Density @ 15°C, g/ml	0.868
KV @ 40°C, cSt	68.0
KV @ 100°C, cSt	11
Viscosity Index	151
Pour point, °C	≥-30°C
Flash point, °C	≥220°C
OIT / Mins	1177